



# STATEMENT OF COMPLIANCE

## BUILDING CODE COMPLIANCE FOR ROOF HATCHES

MKT Roof Hatches sold in New Zealand comply with the performance requirements of New Zealand Building Code Clauses as shown below. Scope of use: MKT Roof Hatches must be used as directed in MKT Technical Information and installation instructions available.

| New Zealand Building Code Clauses | Compliance Documents                    |                                |  |
|-----------------------------------|---|--------------------------------|--|
| B2/AS1                            | Durability                              | AS4285 - 2007                  | MKT Roof Hatches satisfy the durability requirements specified for Non-structural Roof Cladding elements and External Window/Door Joinery. MKT Roof Hatches have passed tests for weather tightness, concentrated load, non-cyclonic and cyclonic wind pressures according to Australian Standard AS4285 test methods. |
| E2                                | External Moisture                       | AS4285 - 2007                  | MKT Hatches have passed tests for weather tightness, concentrated load, non-cyclonic and cyclonic wind pressures according to Australian Standard AS4285 test methods  |
| H1                                | H1/AS1, 2.1.2 Building Thermal Envelope | NZS4218 Table 4 Climate Zone 3 | Acceptable solution shows Roof Hatches to have a minimum R value of 0.34.  |
| G4/AS1                            | Natural Ventilation (1.2, 2.1)          |                                | MKT Roof Hatches can be used to meet the G4 Natural Ventilation requirements.  |
| G7                                | Natural Light                           |                                | MKT Roof Hatches can be used to meet the G7 Natural Light requirements.  |