

BPIR DECLARATION

Version 1.0 December 2023



COMPANY DETAILS

Name: Monkeytoe Ltd
Role: Manufacturer & Supplier
NZBN: 9429033967882
Address: 45 Mawhitiwhiti Rd, Normanby 4614, Taranaki, NZ
Website: <https://www.monkeytoe.co.nz/>
Email: sales@monkeytoegroup.com
Phone: 0800 454 808

PRODUCT DETAILS

Building Product Class	Class 1
Product name/line	Gutterguards
Product Identifier	Skyguard / Gutter Covers / Gutter & Snow Guard
Place of Manufacture	Extrusions, fittings- NZ, overseas; FRP - overseas

PRODUCT DESCRIPTION

Proprietary aluminium or fiber reinforced plastic (FRP) trafficable decking/walkway modules to prevent gutters filling with snow or leaves.

SCOPE OF USE

- Gutter systems of any width - manufactured in widths 200-600mm, and for wider gutters multiple modules are used.
- Gutters which require leaf or snow protection
- Can be upgraded to be trafficable
- Hail guards

CONDITIONS OF USE

- Supplied in sections of 1.2-2.4m to allow for easy of removal to clean gutters
- Gutter is able to take the additional loads imposed
- Flow rate of gutter is not reduced
- Separation between gutter and guard is 4mm
- Max width of 600mm per module, use multiple modules for wider gutters
- Max height of 200mm
- Not exposed to high winds or Cyclone prone locations

Must be installed by an approved installer and maintained as per Monkeytoe product guides, warranty and maintenance documentation.

ASSOCIATED PRODUCTS

N/A

RELEVANT BUILDING CODE CLAUSES

B1 Structure: 3.1-3.4

B2 Durability: 3.1c,

D1 Access Routes: 3.3d

E2 External Moisture: 3.1, 3.2

F2 Hazardous building materials:

CONTRIBUTIONS TO COMPLIANCE

- B1: Designed to the following Standards:
 - AS/NZS1170.1-2002
 - AS/NZS 1170.2-2021
 - AS/NZS 1170.5-2004
 - AS/NZS1664.1-1997
 - AS/NZS1665-2004
- B1: Manufactured to the following standards:
 - AS/NZS 1886- 1997

BPIR DECLARATION

Version 1.0 December 2023



- B2: Monkeytoe products have a proof of durability as per B2/VM1 with testing and in-service history and similar materials. For more information see the document B2 DURABILITY FOR
- D1: Monkeytoe Gutter Guards are designed and tested against AS 1657:2013 which is an acceptable solution as per D1 11.0.1 D1/AS1 Amendment 6, 2017.
- E2: Monkeytoe Gutter Guards assist the building shed melted snow and also assist in preventing pooling of water which leads to dampness and damage.
- F2: This product contains no hazardous materials

SUPPORTING DOCUMENTATION

The following documentation supports the above statements:

Title (Type)	Version, Date	Date
B2 DURABILITY FOR EXTERNAL ALUMINUM STRUCTURES ON BUILDINGS	2.1	17/11/2023
Gutter & Snow Guard Spec Sheet	5/04/2022	
Skywalk Snow Guard Install Guide	2004-MKT-SG-01	11/06/2018
MKT FRP PRODUCT DESIGN INFORMATION		

Contact Customer Service sales@monkeytoegroup.com or 0800 454 808 for a copy of the above documents

FOR FURTHER INFORMATION

For all design, installation and maintenance related information please refer to: www.monkeytoe.co.nz.

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct. I can also confirm that Monkeytoe Ltd products are not subject to a ban under s26 of the Building Act.

Signed for and on behalf of **Monkeytoe Ltd:**

Jamieson Prestidge

Job Role: Technical Consultant

Date 20/11/2023

Jamieson Prestidge

APPENDIX

Building code performance clauses

All relevant building code performance clauses listed in this document:

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during construction or alteration and throughout their lives.

B1.3.2

Buildings, building elements and sitework shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during construction or alteration when the building is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of buildings, building elements and sitework, including:

- (a) self-weight,
- (b) imposed gravity loads arising from use,
- (c) temperature,
- (d) earth pressure,
- (e) water and other liquids,
- (f) earthquake,
- (g) snow,
- (h) wind,
- (i) fire,
- (j) impact,
- (k) explosion,
- (l) reversing or fluctuating effects,
- (m) differential movement,
- (n) vegetation,
- (o) adverse effects due to insufficient separation from other buildings,
- (p) influence of equipment, services, non-structural elements and contents,
- (q) time dependent effects including creep and shrinkage, and
- (r) removal of support.

B1.3.4

Due allowance shall be made for:

- (a) the consequences of failure,
- (b) the intended use of the building,
- (c) effects of uncertainties resulting from construction activities, or the sequence in which construction activities occur,
- (d) variation in the properties of materials and the characteristics of the site, and
- (e) accuracy limitations inherent in the methods used to predict the stability of buildings.

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (b) 15 years if:

- (i) those building elements (including the building envelope, exposed plumbing in the subfloor space, and in-built chimneys and flues) are moderately difficult to access or replace, or
 - (ii) failure of those building elements to comply with the building code would go undetected during normal use of the building but would be easily detected during normal maintenance.
- (c) 5 years if:
- (i) the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 - (ii) failure of those building elements to comply with the building code would be easily detected during normal use of the building.

D1 Access Routes

D1.3.3

Access routes shall:

- (a) have adequate activity space,
- (b) be free from dangerous obstructions and from any projections likely to cause an obstruction,
- (c) have a safe cross fall, and safe slope in the direction of travel,
- (d) have adequate slip-resistant walking surfaces under all conditions of normal use,
- (e) include stairs to allow access to upper floors irrespective of whether an escalator or lift has been provided,
- (f) have stair treads, and ladder treads or rungs which:
 - (i) provide adequate footing, and
 - (i) not contain isolated steps,
 - (j) have smooth, reachable and graspable handrails to provide support and to assist with movement along a stair or ladder,
 - (k) have handrails of adequate strength and rigidity as required by Clause B1 Structure,
 - (l) have landings of appropriate dimensions and at appropriate intervals along a stair or ramp to prevent undue fatigue,
 - (m) have landings of appropriate dimensions where a door opens from or onto a stair, ramp or ladder so that the door does not create a hazard, and

E2 External Moisture

E2.3.1 Roofs must shed precipitated moisture. In locations subject to snowfalls, roofs must also shed melted snow.

E2.3.2 Roofs and exterior walls must prevent the penetration of water that could cause undue dampness, damage to *building elements*, or both.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.